


1.	Project name	<p>"My first sports area" Installation of sports equipment in the courtyard of a residential building No. 53 on Slobodskaya street.</p> 
2.	Applicant organization offering the project:	Municipal Unitary Enterprise "Housing and Communal Services No. 1 of Moskovsky district of Minsk"
3.	Organization address, telephone, fax, e-mail	Republic of Belarus, Minsk, 26 Gurskogo St., +375 17 362 78 90
4.	Head of the organization	Kazunko Grigory Valerievich, director
5.	Project manager	Sidorenko Ekaterina Aleksandrovna, Deputy Director for Social Affairs and Community Outreach, +375 17 374 34 95 minsk-da@mail.ru
6.	Project term	2022-2023

7.	Project objective	Creation of a sports area for physical exercise, health preservation, instilling healthy lifestyle skills.
8.	Project tasks	<ul style="list-style-type: none"> - To create favorable conditions for physical exercise, sports, leisure and recreation; - To contribute to the formation of a sustainable interest in regular physical exercise and sports.
9.	Target group	children of school age and older
10.	Brief description of activities within the project:	<p data-bbox="671 465 1501 539">Development of design specifications and estimates on improvement and installation of sports equipment</p> <div data-bbox="683 607 1522 1077" style="text-align: center;">  </div> <p data-bbox="671 1149 1538 1910">The complex consists of 16 vertical support pillars, the height from the base of the cover: 2600 mm - 7 pcs (concreting depth 700 mm), 2300 mm - 1 piece (concreting depth 700 mm), 1400 mm - 4 pcs (concreting depth 700 mm), 1100 mm - 2 pcs (concreting depth 700 mm), 450 mm - 2 pcs (concreting depth 550 mm), horizontal bar - 2 crossbars, bench -3 crossbeams, laminated timber beams (width 450 mm, length 1800 mm), ladder section, 2 sections of monkey ladder, P-bars – 4 crossbars. The crossbeams are located at a height of 2300 mm, 2200 mm, 1300 mm, 1300 mm, 1100 mm, 1100 mm, 1100 mm, 1300 mm, 400 mm from the base surface, sections of the monkey ladder - 2200 mm, 2300 mm. The beam is fastened with half-clamps to the horizontal bars of the bench. The fastening of the crossbars to the vertical support pillars is carried out with the help of clamps.</p> <p data-bbox="671 1917 927 1955">Characteristics:</p> <ul style="list-style-type: none"> <li data-bbox="722 1962 1501 2085">• Functions: Abdominal crunch bench, Horizontal bar, Monkey ladder, P-bars, wall-mounted ladder/ladder <li data-bbox="722 2092 1497 2119">• Simultaneous number of attendees: 14 (persons)

- Material: Steel, timber bar
- Number of horizontal bar levels: 2
- Height of horizontal bars: 210 cm, 240 cm
- Diameter of crossbeams of bars: 34 mm.
- Height adjustment: Yes
- Weight: 523 kg
- Dimensions for transportation: 3.3x1.4x0.6 m
- Assembled dimensions: 5.2x5.8x2.6 m

Pillar - Steel pipe with a diameter of 89 mm, a wall thickness of at least 3 mm, ERW Welded Pipe GOST 10705-80/10704-91. Color - black, painting - polyester enamel applied in an electrostatic heat chamber. Support pillars have steel elliptical plugs.

Horizontal bar crossbar - a steel pipe with a diameter of 34 mm with a wall thickness of at least 3.2 mm, Water-supply and gas-supply steel pipes GOST 3262-75. The length of the crossbars is 1200 mm. At the ends of the crossbar there are holes for M10 bolts. Color - black, painting - polyester enamel applied in an electrostatic heat chamber.

Bench crossbeam - a steel pipe with a diameter of 34 mm with a wall thickness of at least 3.2 mm, Water-supply and gas-supply steel pipes GOST 3262-75. The length of the crossbars is 510 mm. At the ends of the crossbar there are holes for M10 bolts. Color - black, painting - polyester enamel applied in an electrostatic heat chamber.

Ladder section - Section width - 1200 mm. The ladder section is solid (one-piece). The ladder section includes seven horizontal rungs made of a pipe with a diameter of 34 mm and a wall thickness of at least 3.2 mm, Water-supply and gas-supply steel pipes GOST 3262-75, and two vertical bearing rungs made of a pipe with a diameter of 48 mm and a wall thickness of at least 3.5 mm, Water-supply and gas-supply steel pipes GOST 3262-75. Color - black, painting - polyester enamel applied in an electrostatic heat chamber. Ladder step - 310 mm.

Monkey ladder section - Section length - 1900 mm, width - 1200 mm. The monkey ladder section is solid (one-piece). The structure of the monkey ladder section includes five horizontal crossbars, made of a pipe with a diameter of 34 mm with a wall thickness of at least 3.2 mm, Water-supply and gas-supply steel pipes GOST 3262-75, and two bearing crossbars made of a pipe with a diameter of 48 mm with a wall thickness of at least 3.5

		<p>mm, Water-supply and gas-supply steel pipes GOST 3262-75. Color - black, painting - polyester enamel applied in an electrostatic heat chamber. Monkey ladder step - 270 mm.</p> <p>P-bars crossbars - a steel pipe with a diameter of 48 mm, wall thickness of at least 3.5 mm, Water-supply and gas-supply steel pipes GOST 3262-75. The length of the crossbars is 1700 mm. At the ends of the crossbar there are holes for M10 bolts. Color - black, painting - polyester enamel applied in an electrostatic heat chamber.</p> <p>Clamp - Designed for rigid connection of 2 mutually perpendicular pipes of different diameters using a threaded joint, consists of two half-rings connected to each other using 2 M10 screws, one of the half-rings can have a through threaded hole for the M10 bolt for the possibility of additional strong fixation on a vertical support pillar. Fulfillment of safety requirements is achieved thanks to the shape with smooth contour lines. Color - orange, painting - polyester enamel applied in an electrostatic heat chamber.</p> <p>Unlike a welded joint, which is done once and for all, the position of the horizontal bars on the clamps can, if required, be changed to your liking. So if you are tired of the usual combination of crossbars, just pick up a hexagon and rearrange the horizontal bars the way you want!!!</p>
11.	Estimated cost of the project	6,697.00 (six thousand six hundred ninety-seven rubles 00 kopecks) Belarusian rubles
12.	Donor funds	6,697.00 (six thousand six hundred ninety-seven rubles 00 kopecks) Belarusian rubles
13.	Co-financing	-